Republic of the Philippines City of San Carlos Negros Occidental

SHEET NO. 1

INVITATION TO BID

PURCHASE REQUEST NO: 1-24-09-1587

Page 1 of 3

Sealed bids for quotation of prices will be received for the purchase of the following supplies, materials and equipment of the government to be opened on the date, place and time stated in INSTRUCTION TO BIDDERS.

ITEM#	QTY.	UNIT	ARTICLES U PRICE	TOTAL
		1	Work Duration: 120 Working Days upon receipt of P.O.	
	- 1		Supply & Installation	
1	3	units	Single Fire Rated Panic Door Complete with Complete	
		001	Accesso <mark>ries (for Fire Exit at Gr<mark>ound F</mark>loor)</mark>	
			Door Height: 2100mm	
			Door Width: 1000mm	
			Door Leaf Thickness: 45mm	
	1		Frame Depth: 130mm Fire Rated Time: 3 Hours	
			Steel Door Frame: 1.5mm Galvanized Steel Sheet	
			Door Leaf Material: 1.0mm Galvanized Steel Sheet	
			Door Leaf and Frame Powder Coated Finish	
			Underwriters Laboratories Certificate	
2	12	units	Bi-Parting Fire Rated Panic Door Complete with	
			Accessories (for Fire Exit at S <mark>econd to S</mark> eventh Floor)	
			Door Height: 2100mm	
			Door Width: 1900mm	
			Door Leaf Thickness: 45mm	
			Frame Depth: 130mm	
			Fire Rated Time: 3 Hours	
			Steel Door Frame: 1.5mm Galvanized Steel Sheet Door Leaf Material: 1.0mm Galvanized Steel Sheet	
			Door Leaf and Frame Powder Coated Finish	
			Underwriters Laboratories Certificate	
3	22	units	Single Fire Rated Panic Door Complete with	
			Accessories (for AC Outdoor Unit Access)	
			Door Height: 2100mm	
			Door Width: 800mm	
			Door Leaf Thickness: 45mm	
			Frame Depth: 130mm	
			Fire Rated Time: 3 Hours	
			Steel Door Frame: 1.5mm Galvanized Steel Sheet Door Leaf Materials: 1.0mm Galvanized Steel Sheet	
			Door Leaf and Frame Powder Coated Finish	
			Underwriters Laboratories Certificate	
4	24	units	Single Fire Rated Panic Door Complete with	
			Accessories (for Pipechase)	
			Door Height: 2100mm	
			Door Width: 700mm	
			Door Leaf Thickness: 45mm	
			Frame Depth: 130mm	
			Fire Rated Time: 3 Hours	

Steel Door Frame: 1.5mm Galvanized Steel Sheet Door Leaf Material: 1.0mm Galvanized Steel Sheet

Door Leaf and Frame Powder Coated Finish

Underwriters Laboratories Certificate

5 2 units Bi-Parting Fire Rated Panic Door Complete with

Accessories (for Storage at Seventh Floor)

Door Height: 2100mm
Door Width: 1600mm
Door Leaf Thickness: 45mm
Frame Depth: 130mm
Fire Rated Time: 3 Hours

Steel Door Frame: 1.5mm Galvanized Steel Sheet
Door Leaf Material: 1.0mm Galvanized Steel Sheet

Door Leaf and Frame Powder Coated Finish

Underwriters Laboratories Certificate

Bi-Parting Fire Rated Panic Door Complete with

Accessories (for Access at Seventh Floor to CDRRMO)

Door Height: 2100mm
Door Width: 1900mm
Door Leaf Thickness: 45mm
Frame Depth: 130mm
Fire Rated Time: 3 Hours

Steel Door Frame: 1.5mm Galvanized Steel Sheet
Door Leaf Material: 1.0mm Galvanized Steel Sheet

Door Leaf and Frame Powder Coated Finish

Underwriters Laboratories Certificate

Note: All Items should be Certificate as Follows:

Handle Lock (UL Certified)

Application: For Rebated of Flush Door Material: Stainless Steel Face Plate Latch Bolt Dead Bead Bolt Spindle

Lock Case: Steel
Striking Box: Plastic
Lock Size: 60 x 72 mm
Application Door: 35-55cm

Closure|: Prepared for Profile Cylinder

Tounge Trip: 2-Turn

Face Plate: Round or Square S/Steel Lever Tube Handle

Suitable for: Wooden Doors / Metal Doors Standard: EN12209-2003 UL Listed Lever Handle Exit Devices (UL Certified)

Material: Stainless Steel Rosette Diameter: 77mm Lever Length 134mm Lever Projection: 56mm Finish: Satin Polish

Non-Handed

Cylinder: Standard Schlage C Keyway

Fits Standard Door Preps

Spindle Structure Supplied with 3 Keys ADA Compliant

Panic Exit Device for Single Leaf Door (UL Certified)

Type: Rim Type, Half Length or Full Length Material: Heavy Gauge Steel or Stainless Steel

6

1

unit

Length: 1045mm as a Standard, Could be Customized

Color: Silver Painted or Stainless Steel as a Standard, Could be Customized

Accomodates Wood and Metal Doors with Thru Bolts Standard

Apply to Door for Fire Protection, Smoke Ventilation

Apply to Single Leaf Door

Could be Match with Outside Access Device Like Cylinder, Trim and Lever

Conforming to ANSI / BHMA Standard A 156.3 Grade 1

Open by Handspike Inside, and bu Key Outside

Endurance Test, Over 500.000 Times Still Keep Good Performance

Surface Mounted for Ease of Installation

None Fire Rated Devices Come Standard with Hex Key Dogging

Dogging: Allen Key Hinge (UL Certified)

Stainless Steel 4 Ball Bearing Hinge Materials: SUS304 Stainless Steel

Finish: SSS PSS PVD AB AC

Optional Size: Dimention (H x W x T) 4.5" x 4.0" x 3.0mm Panic Exit Device for Single Leaf Door (UL Certified)

Type: Rim Type, Half Length or Full Length Material: Heavy Gauge Steel or Stainless Steel

Length: 1045mm as a Standard, Could be Customized

Color: Silver Painted or Stainless Steel as a Standard, Could be Customized

Accomodates Wood and Metal Doors with Thru Bolts Standard

Match with Outside Access Device Like, Trim and Lever

Automatic Top and Bottom Latches Maintaining the Bolt Drawn in when the Door is open

Conforming to ANSI / BHMA Standard A 156.3 Grade 1

Endurance Test, Over 500,000 Times Still Keep Good Performance

Surface Mounted for Ease of Installation

Door Height: 2100MM as Sta<mark>ndard, other Door Height can be Cu</mark>stomized Latch: No Latch Required in Panic Exit Device, 2-Point Function by Vertical Rod

Screw: Screw Bolt, Metal Screw and Wood Screw

None Fire Rated Devices Come Standard with Hex Key Dogging

Dogging: Allen Key

Technological Data

Door Closed (UL Certified)

The Max Width of Door is 900 - 1300mm, Suitable for the Door Weigth of 60-90kgs With a Function of Stopping at Anchor Point 90° and no Anchor Point of 180°

Distance: 188mm x 19mm

Maximum Width Door Leaf: ≤1300mm Available Bearing Weight: 60-90kgs Types of Rocking Arm: 360° Adjustable

Speed Governing Control: Two Stage Adjustable Speed

Maximum Opening Angle: 180°

Orienting Function: Non Hold Open and Hold Open

Life Open: >5000,000 Times

Warranty: 1 Year

PURPOSE: For use of Supply with Installation of Panic Doors and Steel TOTAL

Doors for the 6-Storey City Hall Annex Building.

Company Name / Business Name & Address	Name / Signature of Representatives	Form & Amount
		of Bid Security

INSTRUCTION TO BIDDERS

PURCHASE REQUEST NO : 1-24-09-1587 DATE: September 9, 2024

FOR USE OF SUPPLY WITH INSTALLATION OF PANIC DOORS AND STEEL DOORS FOR THE 6-**PURPOSE:**

STOREY CITY HALL ANNEX BUILDING

OFFICE:

DATE OF OPENING & DEADLINE FOR THE SUBMISSION OF BIDS: 1:30 P.M., October 15, 2024

PLACE: BAC Secretariat Office/CMO Extension Office

AMOUNT OF CONTRACT

BID SECURITY Surety Bond

Cash/ Manager's Check (5% of ABC) (2% of ABC)

4,567,500.00 : 91,350.00 : 228,375.00

October 3, 2024 at 8:30 AM, BAC Secretariat Office PRE-BID CONFERENCE:

TERMS & CONDITIONS

The Bid/Bids shall be accompanied by a BID SECURITY in any of the following forms:

a) Cash or cashier's / Manager's Check issued by a Universal <mark>or Commercial Bank</mark> in favor of City Treasurer of San Carlos City.

: Two percent (2%) of the ABC (See above)

: Two percent (2%) of the ABC (See above)

b) Bank draft/guarantee or irrevocable letter of credit issued by a Universal or Commercial Bank: Provided, however, that it shall be confirmed or authenticated by a Universal or Commercial Bank,

if issued by a foreign bank.

c) Surety Bond callable upon demand issued by a surety or insurance company duly certified by the Insurance Commission as authorized

: Five percent (5%) of the ABC (See above)

to issue such security.

d) Any combination of the foregoing

: Proportionate to share form with respect

to total amount of security

e) Bid Securing Declaration

2. Secure bidding documents from the BAC Secretariat Office at a non-refundable fee of (per City Ordinance No. 23-21, Series of 2023.)

P5,000.00

- Sample or Brochures of the materials (if required) shall be attached to the bid documents. 3.
- Your price offer must be valid for 120 calendar days. 4.
- 5. Award will be made to the Lowest Calculated Responsive Bid (LCRB) that is the most advantageous to the government subject to post evaluation by the BAC.
- Submit Omnibus Sworn Statement duly notarized, together with your bid. 6.
- 7. The government reserves the right to reject any or all bids, declare a failure of bidding or not award the contract based on RA 9184.
- 8. Electronic submission and receipt of bids is not available pending compliance with GPPB Resolutions.

SGD ATTY. ESTEFANIO S. LIBUTAN, JR. City Administrator / BAC Vice-Chairman **BIDS & AWARDS COMMITTEE**